



From Bucket Dredges to Shaker Plants The Evolution of Placer Gold Recovery

**Infinity Turbine
LLC**

[TEL] +1-608-238-6001 (Chicago)

[Email] greg@infinityturbine.com

<https://www.infinityturbine.com/placer-gold-recovery-wash-plants-from-shaker-to-trommel-and-bucket-dredges-by-infinity-turbine.html>

A technical assessment comparing historic bucket dredges with modern shaker and trommel wash plants, explaining why shaker plants dominate fine placer gold recovery today.



This webpage QR code

PDF Version of the webpage (maximum 10 pages)

Most Efficient Wash Plant for Placer Gold < 1/4 Inch

For placer gold recovery (particles < 1/4 inch / 6 mm) the most efficient wash plant design combines effective gravimetric concentration with high throughput, minimal gold losses, and adaptability to varying material types (sand, gravel, clay). As a mining engineer specializing in gold recovery, the following outlines the best solution and why.

Most Efficient Wash Plant for Placer Gold < 1/4 Inch

Multi-Stage Trommel with Integrated Sluice and Fine Recovery System (e.g., Hydrocyclone + Centrifugal / Shaker Table / Falcon®)

This configuration is widely regarded as the most efficient for fine placer gold (< 6 mm), and especially for minus 1/4 inch feed because:

1. Trommel provides effective initial screening, separating fines from oversize rock and crushing/clay aggregations.
2. Sluice boxes deliver coarse gold retention via riffles and mats.
3. Fine recovery units (hydrocyclones + centrifugal concentrators or shaking tables) recover gold not captured in the sluice, particularly particles in the 0-1/8 inch and micron fractions.

This multi-stage approach maximizes recovery across a wide PSD (particle size distribution), which is critical for placer gold ores that often contain significant fine gold.

Key Components and Their Roles

1. Trommel Screen

Function: Separates material by size; removes oversize rock that can carry heavy tramp material and interfere with downstream recovery.

Design Considerations:

Drum aperture ~ 1/4 inch (6 mm) or finer for focused recovery.
Gentle tumbling action to minimize gold plating and abrasion.
Water spray/cascade to break clay lumps and wash material clean.

Advantages:

High throughput
Reduced blinding
Improved liberation of gold from matrix

2. Sluice Box (Primary Recovery)

Function: Recovers coarse gold via gravity concentration against riffles and high-friction matting.



Placer-gold recovery practice and commercial wash-plant deployment.

Engineering Assessment

Trommel-Based Wash Plant vs Shaker-Type Wash Plant for Placer Gold under 1/4 Inch

1. Fundamental Process Difference

Trommel Wash Plant

Uses a rotating cylindrical screen for classification

Material is lifted and dropped repeatedly, relying on tumbling and water spray for washing

Gold recovery occurs downstream, typically via sluice boxes and fine-gold circuits

Shaker-Type Wash Plant

Uses vibrating or oscillating flat decks for classification

Material stratifies by density and size through vibration and water flow

Gold recovery occurs immediately on the shaker deck and downstream sluices

2. Recovery Efficiency Comparison

Gold Liberation and Stratification

Trommel

Strong at breaking clay balls and washing sticky gravels

However, tumbling can:

Plate fine gold onto steel surfaces

Carry fine gold forward with slurry if water velocity is not tuned

Requires secondary recovery systems for fine gold

Shaker Plant

Vibration actively stratifies material by density

Gold settles rapidly against riffles or mats

Fine gold remains in contact with recovery surfaces longer

Advantage: Shaker plant, especially for fine gold under 1/8 inch

Fine Gold Retention

Trommel
6/30/2026

Placer-gold recovery practice and commercial wash-plant deployment.

Engineering Assessment

Trommel-Based Wash Plant vs Shaker-Type Wash Plant for Placer Gold under 1/4 Inch

1. Fundamental Process Difference

Trommel Wash Plant

Uses a rotating cylindrical screen for classification
Material is lifted and dropped repeatedly, relying on tumbling and water spray for washing
Gold recovery occurs downstream, typically via sluice boxes and fine-gold circuits

Shaker-Type Wash Plant

Uses vibrating or oscillating flat decks for classification
Material stratifies by density and size through vibration and water flow
Gold recovery occurs immediately on the shaker deck and downstream sluices

2. Recovery Efficiency Comparison

Gold Liberation and Stratification

Trommel

Strong at breaking clay balls and washing sticky gravels
However, tumbling can:

Plate fine gold onto steel surfaces
Carry fine gold forward with slurry if water velocity is not tuned
Requires secondary recovery systems for fine gold

Shaker Plant

Vibration actively stratifies material by density
Gold settles rapidly against riffles or mats
Fine gold remains in contact with recovery surfaces longer

Advantage: Shaker plant, especially for fine gold under 1/8 inch

Trommel Wash Plant vs Shaker Wash Plant vs Historic Bucket Dredge for Fine Placer Gold

A century ago, bucket dredges reshaped rivers in the pursuit of gold. Today, precision recovery has replaced brute force. This assessment compares historic bucket dredges with modern trommel and shaker wash plants, revealing why shaker plants have become the preferred solution for fine placer gold and why dredging belongs to mining history rather than its future.

Integrated Engineering Assessment

Trommel Wash Plant vs Shaker Wash Plant vs Historic Bucket Dredge for Fine Placer Gold

1. Process Overview

Trommel Wash Plant

A rotating cylindrical screen that washes and classifies material, rejecting oversize and feeding undersize to sluices and optional fine-gold recovery systems.

Shaker Wash Plant

A vibrating or oscillating deck that classifies and stratifies material by size and density, allowing gold to settle quickly against recovery surfaces.

Bucket Dredge (Historic)

A continuous mechanical excavation system using a chain of buckets that dig material from riverbeds, feed it into onboard trommels or screens, and discharge tailings behind the dredge.

2. Recovery Efficiency for Fine Gold under 1/4 Inch

Trommel

Good liberation of gold from gravels and clay

Fine gold recovery depends heavily on downstream sluice performance

Fine gold losses increase with throughput unless secondary recovery is added

Shaker Plant

Excellent stratification and prolonged contact with recovery surfaces

Superior capture of flat, flaky, and very fine gold


High recovery efficiency without complex secondary systems

Bucket Dredge

Designed primarily for volume, not precision recovery

Recovery relied on long sluices and coarse riffles

Fine gold losses were historically significant and accepted due to scale



Copyright 6/30/202 Infnity Turbine LLC
